

Upholstery Collections
Finishes blz 31

PEDRALI®

Material for upholstery and cushions

Rivestimenti per imbottiture e cuscini

Legend

Legenda

	CARD	FABRIC	FIRE RETARDANT FABRIC	OUTDOOR FABRIC	GENUINE HARD LEATHER	REGENERATED HARD LEATHER	SIMIL LEATHER	FIRE RETARDANT SIMIL LEATHER	VELVET	FIRE RETARDANT VELVET
Category A	09									
Category B	07									
Category C	04, 05, 07, 10, 11									
Category D	05, 07									
Category E	08									
Category F	13									
Category G	01, 02, 03, 04, 06, 08, 14									
Category H	05, 08, 09, 11, 14									
Category N	03, 08									
Category P	12									

 Fire-retardant Ignifugo	 Outdoor use Adatto per uso esterno
washing / lavaggio	drying / asciugatura
 Do not wash Lavaggio a secco	 Do not tumble dry Non asciugare in asciugatrice
 Hand wash Lavaggio a mano	 Dry flat Asciugare disteso
 Wash at max 30°C normal Lavaggio normale, max 30°C	 Do not wring Non strizzare
 Wash at max 30°C mild Lavaggio delicato, max 30°C	ironing / stiratura
 Wash at max 40°C normal Lavaggio normale, max 40°C	 Do not iron Non stirare
 Wash at max 60°C mild Lavaggio delicato, max 60°C	 Iron at low temperature Stirare a bassa temperatura
dry cleaning / lavaggio a secco	 Iron at medium temperature Stirare a media temperatura
 Do not dry clean Lavaggio a secco non consentito	bleaching / candeggio
 Dry clean, perchlorethylene (PCE) Lavaggio a secco con percloroetilene (PCE)	 Do not bleach Non candeggiare
 Gentle dry cleaning with PCE Lavaggio a secco delicato con PCE	 Any bleaching agent allowed Candeggio consentito

Colors of fabric sample are approximate. Pedrali S.p.A. reserves the right to modify or upgrade the products without prior notice.
I colori dei campioni tessuto sono indicativi. Pedrali S.p.A. si riserva la facoltà di apportare modifiche o migliorie senza alcun preavviso.

Fabrics

Tessuti

Category G

PEDRALI®

FABRICS / TESSUTI



	G59÷G69 G190÷G197	G70÷G78	G140÷G146
COMPOSITION COMPOSIZIONE	90% New wool 10% Nylon	90% New wool 10% Nylon	45% Recycled wool 45% New wool 10% Nylon
ABRASION ABRASIONE	100.000 cycles Martindale (DS/EN ISO 12947-2:2016)	80.000 cycles Martindale (DS/EN ISO 12947-2:2016)	50.000 cycles Martindale (DS/EN ISO 12947-2:2016)
RUBBING FASTNESS SOLIDITÀ ALLO SFREGAMENTO	/	/	Dry and Wet 4-5, scale 1-5 (ISO 105-X12)
PILLING	4, scale 1-5 (EN ISO 12945)	3-4, scale 1-5 (EN ISO 12945)	4, scale 1-5 (EN ISO 12945)
LIGHT FASTNESS SOLIDITÀ ALLA LUCE	5-7, scale 1-8 (EN ISO 105-B02)	5-7, scale 1-8 (ISO 105-B02)	5-7, scale 1-8 (ISO 105-B02:2014)
SOUND ABSORPTION ASSORBIMENTO ACUSTICO	folded: α_w = 0.95 Class A (ISO 11654)	folded: α_w = 0.80 Class B (ISO 11654)	folded: α_w = 0.75 Class C (ISO 11654)
FLAME RESISTANCE RESISTENZA AL FUOCO	AS/NZS 1530.3 AS/NZS 3837 Class 2 BS 5852 Part 1 BS 5852 Crib 5 with treatment BS 5852 IGNITION SOURCE 3 EN 1021 – 1/2 GB 50222 B1 with treatment IMO FTP Code 2010: Part 8 NF D60-013 NFPA 260 ÖNORM B1/Q1 SN 198 898 5.3 with treatment UNI 9175 Classe 1 IM US CA TB 117-2013	AS/NZS 1530.3 BS 5852 crib 5 with treatment BS 5852 part 1 EN 1021-1/2 IMO FTP Code 2010 Part 8 NF D 60 013 NFPA 260 SN 198 898 5.3 with treatment UNI 9175 1IM US Cal. Bull. 117-2013	AS/NZS 1530.3 AS/NZS 3837 Class 2 BS 5852 Part 1 BS 5852 Crib 5 with treatment BS 5852 IGNITION SOURCE 3 EN 1021 – 1/2 IMO FTP Code 2010: Part 8 NF D60-013 ÖNORM B1/Q1 UNI 9175 Classe 1IM US CA TB 117-2013
APPROVED OMOLOGATO	PRODUCT CERTIFIED FOR LOW CHEMICAL EMISSIONS: UL COM/CG UL 2318 170166-420		
CLEANING LAVAGGIO			



Collection / Collezione

• kvadrat

STEELCUT TRIO

from G59 to G69


from G190 to G197

STEELCUT


from G70 to G78

DESIGNERS Dijkmeijer & Ridolfo


G 59




G192



G 69




G 190




G 191




G 72




G 67



G 78




G 193




G 194




G 195




G 196



G 75



G 197



G 68




G 66



G 71



G 64




G 61




G 60



G 65




G 74



G 63




G 73



G 62



G 70



G 143



G 145



G 144



G 146



G 140



G 141



G 142



Collection / Collezione

• kvadrat

RE-WOOL

from G140 to G146

DESIGNER Margrethe Odgaard

Fabrics

Tessuti

Category G

PEDRALI®

FABRICS / TESSUTI



	G21÷G25 G110÷G116	G160÷G169	G01÷G09
COMPOSITION COMPOSIZIONE	100% New wool	96% New wool 4% Nylon	88% Polyester 12% Polyurethane
ABRASION ABRASIONE	45.000 cycles Martindale (EN ISO 12947)	45.000 cycles Martindale (EN ISO 12947)	150.000 cycles Martindale (EN ISO 12947)
RUBBING FASTNESS SOLIDITÀ ALLO SFREGAMENTO	/	/	Dry 5 and Wet 4/4, scale 1-5 (ISO 105-X12)
PILLING	3, scale 1-5 (EN ISO 12945)	3-4, scale 1-5 (EN ISO 12945)	5, scale 1-5 (EN ISO 12945)
LIGHT FASTNESS SOLIDITÀ ALLA LUCE	5-7, scale 1-8 (ISO 105-B02)	5-7, scale 1-8 (ISO 105-B02)	5-6, scale 1-8 (ISO 105-B02)
SOUND ABSORPTION ASSORBIMENTO ACUSTICO	folded: α_w =0.70 Class C (ISO 11654)	folded: α_w =0.75 Class C (ISO 11654)	/
FLAME RESISTANCE RESISTENZA AL FUOCO	AS/NZS 1530.3 BS 5852 Crib 5 BS 5852 Part 1 BS 5867 part 2 type B EN 1021-1/2 EN 13501, C-s1, d0, glued GB 50222 B1 with treatment IMO FTP Code 2010: Part 8 NF D60-013 NFPA 260 ÖNORM B1/ Q1 SN 198 898 5.3 with treatment UNI 9175 Classe 1 IM US CA TB 117-2013	AS/NZS 3837 Class 2 BS 5852 Crib 5 with treatment BS 5852 Part 1 EN 1021 – 1/2 IMO FTP Code 2010: Part 8 IMO FTP Code 2010: Part 7 with treatment NF D60-013 SN 198 898 5.3 with treatment UNI 9175 Classe 1 IM US CA TB 117-2013	BS EN 1021 1&2 BS EN 1021- ÖNORM A3800-B2-B3825-Q1 UK NF P 92-503 M3 US CA TB 117-2013
APPROVED OMOLOGATO	   PRODUCT CERTIFIED FOR LOW CHEMICAL EMISSIONS: UL COM/IGG UL 2818 170166-420		/
CLEANING LAVAGGIO			



Collection / Collezione

• kvadrat

DIVINA MELANGE
from G21 to G25

DIVINA MD
from G110 to G116

DESIGNER Finn Skødt

G 24



G 114




G 115




G 113




G 111



G 116



G 110



G 112



G 21




G 25




G 22



G 23



G 163



G 160



G 161



G 162



G 165



G 166




G 167



G 168



G 164



G 169



G 08



G 07



G 01



G 09



Fabrics
Tessuti

Category G | N

PEDRALI®

FABRICS / TESSUTI

	G		N	
	G100÷G102	G120÷G122	G220÷G225	N01÷N08
COMPOSITION COMPOSIZIONE	90% New wool 10% Nylon	100% New wool	52% Cotton 22% Viscose 14% Polyacrylic 6% Linen 3% Nylon 3% Polyester	58% New wool 25% Viscose 8% Linen 5% Nylon 4% Polyester
ABRASION ABRASIONE	50.000 cycles Martindale (EN ISO 12947-2:1998)	75-100.000 cycles Martindale (EN ISO 12947-2:1998)	50.000 cycles Martindale (EN ISO 12947)	50.000 cycles Martindale (EN ISO 12947)
PILLING	4, scale 1-5 (EN ISO 12945)	3-4, scale 1-5 (EN ISO 12945)	4-5, scale 1-5 (EN ISO 12945)	3, scale 1-5 (EN ISO 12945)
LIGHT FASTNESS SOLIDITÀ ALLA LUCE	6-7, scale 1-8 (ISO 105-B02)	6-7, scale 1-8 (ISO 105-B02)	5-7, scale 1-8 (ISO 105-B02)	N03, N04: 5-7, scale 1-8 (ISO 105-B02) N01, N02, N05+N08 4-7, scale 1-8 (ISO 105-B02)
RUBBING FASTNESS SOLIDITÀ ALLO SFREGAMENTO	/	/	/	N01, N02, N05+N08 Dry 4-5 and Wet 3-5, scale 1-5 (EN ISO 105-X12)
FLAME RESISTANCE RESISTENZA AL FUOCO	AS/NZS 3837 Class 2 BS 5852 Part 1 BS 5852 Crib 5 with treatment EN 1021 – 1/2 GB 50222 B1 with treatment IMO FTP Code 2010: Part 8 NFPA 260 NF D60-013 ÖNORM B1/Q1 SN 198 898 5.3 with treatment UNI 9175 Classe 1 IM US CA TB 117-2013	BS 5852 Part 1 BS 5852 Crib 5 with treatment EN 1021 – 1/2 IMO FTP Code 2010: Part 8 NFPA 260 NF D60-013 ÖNORM B1/Q1 UNI 9175 Classe 1IM US CA TB 117-2013	BS 5852 crib 5 with treatment BS 5852 part 1 EN 1021-1/2	N03, N04: AS/NZS 3837, class 2 BS 5852 Part 1 BS 5852 Crib 5 with treatment DIN 4102 B2 EN 1021 – 1/2 NFPA 260 US CA TB 117-2013 N01, N02, N05+N08 AS/NZS 3837, class 2 BS 5852 Part 1 with treatment BS 5852 Crib 5 with treatment EN 1021 – 1/2 IMO FTP Code 2020: Part 8 with treatment NFPA 260 US CA TB 117-2013
APPROVED OMOLOGATO	PRODUCT CERTIFIED FOR LOW CHEMICAL EMISSIONS: UL.COM/GG UL 2818 170166-420		/	
CLEANING LAVAGGIO				



G

Collection / Collezione


• **kvadrat**

BASEL


from G100 to G102

DESIGNERS Herzog & de Meuron


G 101



G 100



G 102



G 120



G 121



G 122



G 225



G 220



G 221



G 222



G 223



G 224



N

Collection / Collezione

• **kvadrat**


SUNNIVA

from N01 to N08

DESIGNERS

Raf Simons & Fanny Aronsen


N 05



N 01




N 02



N 03



N 04



N 06



N 07



N 08



Fabrics

Tessuti

Category C | G

PEDRALI®

FABRICS / TESSUTI

	C 	G 
	C110÷C122	G150÷G156
COMPOSITION COMPOSIZIONE	85% Wool 15% Polyamide	82% Wool 12% Rami 6% Polyamide
ABRASION ABRASIONE	100.000 cycles Martindale (EN ISO 12947-2)	100.000 cycles Martindale (EN ISO 12947-2)
RUBBING FASTNESS SOLIDITÀ ALLO SFREGAMENTO	Dry 4 and Wet 3-4, scale 1-5 (EN ISO 105-X12)	Dry 4 and Wet 3-4, scale 1-5 (EN ISO 105-X12)
LIGHT FASTNESS SOLIDITÀ ALLA LUCE	5-7, scale 1-8 (EN ISO 105-B02)	5-7, scale 1-8 (EN ISO 105-B02)
FLAME RESISTANCE RESISTENZA AL FUOCO	BS 5852 Crib 5 EN ISO 1021 part 1&2 IMO FTP Code 2010: Part 8 UNI 9175 Classe 1 IM	BS 5852 Crib 5 EN ISO 1021 Part 1&2 IMO FTP Code 2010: Part 8 UNI 9175 Classe 1 IM US CA TB 117-2013
APPROVED OMOLOGATO	 	
CLEANING LAVAGGIO	    	    



C

Collection / Collezione


•  **svensson**

SEMI
from C110 to C122


C110



C111




C112




C113




C117



C118



C119




C115




C116




C120




C121



C122



C114




G

Collection / Collezione


•  **svensson**

BALANCE
from G150 to G156


G 154




G 155



G 156




G 151




G 150



G 152



G 153



Fabrics
Tessuti

Category C | D | H

PEDRALI®


FABRICS / TESSUTI

	C 	D 	H 
	C83÷C89 C100, C101	D40÷D44	H60÷H64
COMPOSITION COMPOSIZIONE	54% New Zealand Wool 44% Post-consumer recycled, polyester 2% Polyamide	88% New Zealand Wool 12% Polyamide	92% New Zealand Wool 8% Polyamide
ABRASION ABRASIONE	100.000 cycles Martindale (EN ISO 12947-2)	100.000 cycles Martindale (EN ISO 12947-2)	200.000 cycles Martindale (EN ISO 12947-2)
RUBBING FASTNESS SOLIDITÀ ALLO SFREGAMENTO	Dry and Wet 4-5, scale 1-5 (EN ISO 105-X12:1995)	Dry and Wet 4-5, scale 1-5 (EN ISO 105-X12)	Dry and Wet 4-5, scale 1-5 (EN ISO 105-X12)
PILLING	4-5, scale 1-5 (EN ISO 12945-2)	4-5, scale 1-5 (EN ISO 12945-2)	4, scale 1-5 (EN ISO 12945-2)
LIGHT FASTNESS SOLIDITÀ ALLA LUCE	5-7, scale 1-8 (EN ISO 105-B02)	5-7, scale 1-8 (EN ISO 105-B02)	5-7, scale 1-8 (EN ISO 105-B02)
FLAME RESISTANCE RESISTENZA AL FUOCO	BS EN 1021 1&2 BS EN 1021-1 ÖNORM A3800-1 US CA TB 117-2013	BS EN 1021 1&2 BS 5852 Part 1 0, 1 UNI 9175 Classe 1 IM US CA TB 117-2013	BS EN 1021 1&2 BS EN 1021-1 BS 5852 Part 1 0, 1 UNI 9175 Classe 1 IM US CA TB 117-2013
APPROVED OMOLOGATO			
CLEANING LAVAGGIO			




C


C 101




C 86




C 85



C 89




C 83




C 100




C 84



C 88




C 87



D


D 40



D 41




D 43



D 44



D 42



H

H 60



H 61



Fabrics
Tessuti

Category G

PEDRALI®


FABRICS / TESSUTI

	G	
	G130÷G133	G170÷G176; G210÷G213
COMPOSITION COMPOSIZIONE	95% Virgin Wool 5% Polyamide	96% Virgin Wool 4% Polyamide
ABRASION ABRASIONE	52.000 cycles Martindale (DIN EN ISO 12947-2)	90.000 cycles Martindale (DIN EN ISO 12947-2)
PILLING	4-5, scale 1-5 (EN ISO 12945-2)	4-5, scale 1-5 (EN ISO 12945-2)
LIGHT FASTNESS SOLIDITÀ ALLA LUCE	5-8, scale 1-8 (EN ISO 105-B02)	5-8, scale 1-8 (EN ISO 105-B02)
SOUND ABSORPTION ASSORBIMENTO ACUSTICO	folded: α_w =0.85 Class B (ISO 11654)	folded: α_w =0.95 Class A (ISO 11654)
FLAME RESISTANCE RESISTENZA AL FUOCO	BS 5852:1979 (Part 1) BS 5852:2006 (Part 2) Crib 5 DIN 4102-1 B2 EN 1021 -1 and -2 EN 13501-1 FAR 25.853 (12 sec. vertical) IMO: 2014/90/EU (MED) UNI 9175 Classe 1 IM US CA TB 117-2013	BS 5852:1979 (Part 1) BS 5852:2006 (Part 2) Crib 5 DIN 4102-1 B2 EN 13501-1 EN 1021 -1 and -2 FAR 25.853 (12 sec. vertical) IMO: 2014/90/EU (MED) UNI 9175 Classe 1IM US CA TB 117-2013
APPROVED OMOLOGATO		
CLEANING LAVAGGIO		



G

G 130



G 131




G 132




G 133




G 170




G 171



G 172




G 173



G 174



G 175




G 176



G 210



G 211



G 212



G 213



Fabrics
Tessuti

Category B | C | D☀️

PEDRALI®

FABRICS / TESSUTI

	B	C	D☀️	
	B01÷B02	C36÷C39	D31÷D39	D22÷D26
COMPOSITION COMPOSIZIONE	100% Nylon (Support film PVC)	94% Cotton 6% Polyamide	100% Acrylic teflon	100% Polypropylene
ABRASION ABRASIONE	>50.000 cycles, Martindale (UNI EN ISO 12947:00)	40.000 cycles, Martindale (BS EN ISO 12947-2 1999)	10.000 cycles, Martindale (EN ISO 12947)	> 30.000 cycles, Martindale (UNI EN ISO 12947-2)
RUBBING FASTNESS SOLIDITÀ ALLO SFREGAMENTO	5, scale 1-5 (UNI EN ISO 105 X12:97)	Dry 4-5 and Wet 2-3, scale 1-5 (BS EN ISO 105-X12:1995)	/	Dry and Wet 4-5, scale 1-5 (UNI EN ISO 105-X12)
PILLING	5, scale 1-5 (UNI EN ISO 12945-2:00)	4, scale 1-5 (BS EN ISO 12945-2:2001 to 5.000 cycles)	/	5, scale 1-5 (ISO 12945-2 to 5.000 cycles)
LIGHT FASTNESS SOLIDITÀ ALLA LUCE	5, scale 1-8 (UNI EN ISO 105-B02:01)	4-5 (light colours) 5 (medium-dark colours) (BS EN ISO 105-B02:2001)	7-8, scale 1-8 (EN ISO 105-B02)	7, scale 1-8 (EN ISO 105-B02)
WATER FASTNESS SOLIDITÀ ALL'ACQUA	/	/	/	5, scale 1-5 (EN ISO 105-E01)
FLAME RESISTANCE RESISTENZA AL FUOCO	/	/	/	US CA TB 117-2013
CLEANING LAVAGGIO				

B

B 01



B 02



only for collection / solo per collezione




Island

C


C 37



C 38



C 39




C 36



D

collections only for outdoor
collezioni solo per outdoor

D 37




D 38



D 33




D 34




D 39




D 35




D 32



D 31



D 36




only for outdoor / solo per outdoor

for cushions only for collections / solo per cuscino delle collezioni




Intrigo

Nolita




Panarea



Pasha


Plus

Plus Air




Sunset

Reva and Reva Twist



Rail



Reva

Collection / Collezione

• **PEDRALI**


BREZZA

from D22 to D26

D 22




D 23




D24



D 25



D 26



Fabrics

Tessuti

Category G | H

PEDRALI®

FABRICS / TESSUTI

	G 	H 
	G200÷G206	H110÷H117
COMPOSITION COMPOSIZIONE	92% New wool 8% Nylon	100% TREVIRA CS®
ABRASION ABRASIONE	80.000 cycles Martindale (EN ISO 12947)	80.000 cycles Martindale (EN ISO 12947)
PILLING	4, scale 1-5 (EN ISO 12945)	4-5, scale 1-5 (EN ISO 12945)
RUBBING FASTNESS SOLIDITÀ ALLO SFREGAMENTO	Dry 4-5 and Wet 3-5, scale 1-5 (EN ISO 105-X12)	Dry and Wet 4-5, scale 1-5 (EN ISO 105-X12)
LIGHT FASTNESS SOLIDITÀ ALLA LUCE	6-7, scale 1-8 (EN ISO 105-B02)	5-7, scale 1-8 (EN ISO 105-B02)
SOUND ABSORPTION ASSORBIMENTO ACUSTICO	/	folded: α _w =0.50 Class D (EN ISO 354)
FLAME RESISTANCE RESISTENZA AL FUOCO	AS/NZS 1530.3 BS 5852 Part 1 BS 5852 Crib 5 with treatment BS 5852 ignition source 3 EN 1021-1/2 IMO FTP Code 2010: Part 8 NF D60-013 SN 198 898 5.3 with treatment UNI 9175 Classe 1IM US CA TB 117-2013	AS/NZS 3837 class 2 BS 5852 Crib 5 BS 5852 Part 1 with treatment DIN 4102 B1 EN 1021-1/2 IMO FTP Code 2010: Part 8 NF D60-013 NF P92 507 M1 NFPA 701 ÖNORM B1/Q1 SN 198 898 5.2 UNI 9177 Classe 1 US CA TB 117-2013
APPROVED OMOLOGATO	 PRODUCT CERTIFIED FOR LOW CHEMICAL EMISSIONS: UL.COM/GG UL 2818 170168-420	
CLEANING LAVAGGIO		



G

Collection / Collezione

• **kvadrat**

JAALI

from G200 to G206

DESIGNER Doshi Levien

G 200



G 201



G 202



G 203




G 204



G 205



G 206



H

Collection / Collezione

• **kvadrat**

RELATE


from H110 to H117

DESIGNER Patricia Urquiola


H 110



H 111



H 112




H 113




H 114



H 115



H116



H 117



Simil Leather

Finta Pelle

Category C

PEDRALI®

SIMIL LEATHER / FINTA PELLE



	C45÷C48	C130÷C141	C60÷C64 C90÷C95
COMPOSITION COMPOSIZIONE	80% PVC 18% PES 2% Polyurethane	76% PVC 22% PES 2% Polyurethane	72% PVC 25% Cotton 3% Polyurethane
ABRASION ABRASIONE	50.000 cycles Martindale (EN ISO 5470-2)	60.000 cycles Martindale (ISO 5470-2)	50.000 cycles Martindale (EN ISO 5470-2)
RUBBING FASTNESS SOLIDITÀ ALLO SFREGAMENTO	Dry and Wet 4-5, scale 1-5 (UNI EN ISO 105-X12)	Dry and Wet 4-5, scale 1-5 (ISO 105-X12)	Dry and Wet 4-5, scale 1-5 (UNI EN ISO 105-X12)
LIGHT FASTNESS SOLIDITÀ ALLA LUCE	/	6, scale 1-8 (ISO 105-B02)	6, scale 1-8 (UNI EN ISO 105-B02)
FLAME RESISTANCE RESISTENZA AL FUOCO	BS 5852 Part 1 0,1 EN 1021-1&2 UNI 9175 Classe 1 IM	BS 5852-1 match test EN 1021 Part 1-2 UNI 9175 Classe 1 IM US CA TB 117-2013	BS 5852-1 Part 1 EN 1021-2 IMO RESOLUTION A.652 (16): 1989 UNI 9175 Classe 1 IM US CA TB 117-2013
CLEANING LAVAGGIO			



C


C 45



C 46



C 47




C 48




C45÷C48
simil-leather non-homogenous shade (vintage effect)
finta pelle in tonalità non omogenea (effetto vintage)

C 62



C 63



C 64




C 60




C 61




C 90



C 94



C 95




C 93



C 92



C 91




C 139




C 140



C 141



C 134



C 130




C 131



C 132



C 133




C 135



C 136



C 137



C 138



Simil Leather

Finta Pelle

Category C | H

PEDRALI®

SIMIL LEATHER / FINTA PELLE

	C 	H 
	C10÷C22	H80÷H89
COMPOSITION COMPOSIZIONE	85% PVC 15% Cotton	63% Polyurethane 29% Cotton 8% PES
ABRASION ABRASIONE	150.000 cycles Martindale (EN ISO 5470-2)	50.000 cycles Martindale (EN ISO 5470-2)
LIGHT FASTNESS SOLIDITÀ ALLA LUCE	≥6, scale 1-8 (EN ISO 105-B02)	5-6, scale 1-6 (EN ISO 105-B02)
FLAME RESISTANCE RESISTENZA AL FUOCO	B2 (DIN 4102) BS 5852 Crib 5 EN 1021.1-2 EN 13501-1 - Cs3do FAR 25853 App F Part 1 IMO RESOLUTION A.652 NF D60-013 - AM 18 NFP 92503 M1 NY/NJ - Port Authority UFAC Fabric Class 1 German fire standard B1 (except C12 and C22) US CATB 117 US CATB 133	BS 5852-1 cigarette test BS 5852-1 match test BS 5852 crib 5 EN 1021-1 EN 1021-2 IMO FTP CODE 2010 TB 117:2013 UNI 9175 classe 1IM
APPROVED OMOLOGATO		/
CLEANING LAVAGGIO		



C


C 14



C 21



C 15



C 17



C 13




C 12




C 20




C 11




C 18



C 22



C 10



H

H 80



H 82



H 85



H 87



H 88



H 89



Simil Leather

Finta Pelle

Category A | H

PEDRALI®

SIMIL LEATHER / FINTA PELLE

	A	H 
	A70÷A96	H20÷H35 H100÷H108
COMPOSITION COMPOSIZIONE	85% PVC 15% Polyurethane	63% Polyurethane 29% Cotton 8% PES
ABRASION ABRASIONE	50.000 cycles Martindale (UNI EN ISO 12947-2)	150.000 cycles Martindale (UNI EN ISO 12947-2)
RUBBING FASTNESS SOLIDITÀ ALLO SFREGAMENTO	Dry and Wet 4-5, scale 1-5 (UNI EN ISO 105-X12)	/
LIGHT FASTNESS SOLIDITÀ ALLA LUCE	6, scale 1-8 (UNI EN ISO 105-B02)	5-6, scale 1-8 (UNI EN ISO 105-B02)
FLAME RESISTANCE RESISTENZA AL FUOCO	/	BS 5852 Crib 5 BS 5852 Part 1-2 EN 1021 Part 1-2 IMO resolution FTP Code 2010 IMO resolution A.652 (16):1989 UNI 9175 Classe 1 IIM US CA TB 117-2013
CLEANING LAVAGGIO		

A

A 96

A 93

A 94

A 95

A 92

A 72

A 91

A 90

A 82

A 70

A 71

A 73

A 80

A 89

H

H 20

H 100

H 101

H 34

H 102

H 107

H 35

H 27

H 31

H 103

H 104

H 28

H 24

H 22

H 23

H 21

H 33

H 105

H 106

H 108

H 32

H 29

H 30

H 26

Leather

Pelle

Category P

PEDRALI®

LEATHER / PELLE

P

	PBI, PLA, PGC, PSA, PGA, PBE, PGN, PTA, PTE, PRO, PGR, PMA, PNE	PGCF, PGRF, PTEF, PMAF	PBS, PCO, PMS, PVE
COMPOSITION COMPOSIZIONE	Mid grain leather Pelle mezzo fiore	Perforated mid grain leather Pelle mezzo fiore traforata	Vintage mid grain leather Pelle mezzo fiore anticata
RUBBING FASTNESS SOLIDITÀ ALLO SFREGAMENTO	Dry (500 Cycles) and Wet (250 Cycles) ≥4 (UNI EN ISO 11640:1998)	Dry (500 Cycles) and Wet (250 Cycles) ≥4 (UNI EN ISO 11640:1998)	Dry (50 Cycles) and Wet (20 Cycles) ≥3 (UNI EN ISO 11640:1998)
LIGHT FASTNESS SOLIDITÀ ALLA LUCE	≥5 (UNI EN ISO 105 B02) (MET.5)	≥5 (UNI EN ISO 105 B02) (MET.5)	≥2/3 (UNI EN ISO 105-B02) (MET.5)
FLAME RESISTANCE RESISTENZA AL FUOCO	BS 5852:1979 BS EN 1021-1-2:2006 IMO RES A652(16)	BS 5852:1979 BS EN 1021-1-2:2006 IMO RES A652 (16)	BS 5852:1979 BS EN 1021-1-2:2006
APPROVED OMOLOGATO			/
CLEANING LAVAGGIO	Clean with a damp cloth using water. Do not use detergents, solvents, bleached, abrasives. Pulire con un panno umido d'acqua. Non usare detersivi, solventi, candeggianti, abrasivi.	Clean with a damp cloth using water. Do not use detergents, solvents, bleached, abrasives. Pulire con un panno umido d'acqua. Non usare detersivi, solventi, candeggianti, abrasivi.	Clean with a damp cloth and warm water. Do not use detergents, solvents, bleached, abrasives. Pulire con acqua calda e un panno umido. Non usare detersivi, solventi, candeggianti, abrasivi.


P

Collection / Collezione



LINEA

PBI



PLA



PGC




PSA



PGA



PBE



PGN



PTA



PTE



PRO



PGR



PMA




PNE




PGCF



PGRF



PTEF



PMAF



only for collections / solo per collezioni



Vic and Vic Metal

Inner part of the back,
upper part of the seat
Lato interno dello schienale
e parte superiore del sedile

Collection / Collezione




TUSCANIA

PBS




PCO



PMS



PVE



only for collections / solo per collezioni



Malmö



Inga

Hard leather

Cuoio

Category F

GENUINE AND REGENERATED
NATURALE E RIGENERATO

PEDRALI®

HARD LEATHER / CUIOIO

F

F01÷F09

Genuine hard leather, tanned with vegetable substances

Cuoio naturale, conciato con sostanze vegetali

F11÷F19

Regenerated hard leather. Tanned leather cuttings and shavings linked with natural rubber lattelx

Cuoio rigenerato. Ritagli e rasatura di cuoio conciato legati con lattice di gomma naturale

COMPOSITION
COMPOSIZIONE

RUBBING FASTNESS
SOLIDITÀ ALLO SFREGAMENTO

Satisfactory up to maximum 700 abrasions in humid environment and 1000 abrasions in dry environment
Soddisfacente sino a max 700 abrasioni all'umido e 1000 abrasioni al secco

Dry and Wet >1000
(UNI EN ISO 11640)

LIGHT FASTNESS
SOLIDITÀ ALLA LUCE

/

4-5
Xenotest Method

FLAME RESISTANCE
RESISTENZA AL FUOCO

/

BS EN 1021 1&2
BS 5852 Part 1
US CA TB 117 E Part 1

CLEANING
LAVAGGIO


Clean with a damp cloth using water
Pulire con un panno umido d'acqua

Clean with a damp cloth using water
Pulire con un panno umido d'acqua




GENUINE HARD LEATHER
CUOIO NATURALE


F 07



F 05



F 01



F 06



F 09



F 08



F 03



F 04



only for collections / solo per collezioni



Fox



Gliss



Inga



Kuadra



Kuadra XL




Malmö




Mood

REGENERATED HARD LEATHER
CUOIO RIGENERATO


F 18



F 11




F 12



F 19



F 13



F 17



only for collections / solo per collezioni



Inga



Kuadra



Kuadra XL

Velvet

Velluto

Category E | H | N | G


PEDRALI®

VELVET / VELLUTO


	E	H 	N 	G 
	E01÷E09	H40÷H53	N20÷N27	G180÷G185
COMPOSITION COMPOSIZIONE	100% Cotton	100% TREVIRA CS®	100% Polyester FR	100% TREVIRA CS®
ABRASION ABRASIONE	50.000 cycles Martindale (ISO 12947-2)	190.000 cycles Martindale (EN ISO 12947-2)	100.000 cycles Martindale (EN ISO 12947)	50.000 cycles Martindale (EN ISO 12947)
RUBBING FASTNESS SOLIDITÀ ALLO SFREGAMENTO	Dry 4-5 and Wet 3-5, scale 1-5 (ISO 105-X12)	Dry and Wet 4-5, scale 1-5 (EN ISO 105-X12)	Dry 5 and Wet 4-5, scale 1-5 (EN ISO 105-X12)	Dry and Wet 4-5, scale 1-5 (EN ISO 105-X12)
PILLING	/	5, scale 1-5 (EN ISO 12945-2)	4, scale 1-5 (EN ISO 12945-2)	4-5, scale 1-5 (EN ISO 12945)
LIGHT FASTNESS SOLIDITÀ ALLA LUCE	4-6, scale 1-8 (ISO 105-B02)	5, scale 1-8 (EN ISO 105-B02)	4-6, scale 1-8 (EN ISO 105-B02)	5-7, scale 1-8 (ISO 105-B02:2014)
SOUND ABSORPTION ASSORBIMENTO ACUSTICO	/	folded: α _w =0.70 (EN ISO 354:2003)	folded: α _w =0.80 Class B (ISO 11654)	folded: α _w =0.85 Class B (ISO 11654)
FLAME RESISTANCE RESISTENZA AL FUOCO	/	BS 5852 Part 0,1 DIN 4102 B1 EN 1021-1&2 IMO MSC 307(88) Annex 1 Part 7-8 NF P 92-503-507 M1 NFPA 260:2019 UNI 9177 Classe 1 UNI 9175 Classe 1 IM US CA TB 117-2013	BS 5852 Crib 5 BS 5867 part 2 type B DIN 4102 B1 EN 1021-1/2 IMO FTP Code 2010 Part 8 NFPA 701 ÖNORM B1/Q1 SN 198 898 5.2 UNI 9175 1IM US Cal. Bull. 117-2013	ASTM E84 class A BS 5852 Crib 5 BS 5852 Part 1 BS 5867 Part 2 type B DIN 4102 B1 EN 1021-1/2 EN 13501-1, B-S1, d0 IMO FTP Code 2010:Part 8 NF D60-013 NF P92 507 M1 NFPA 701 ÖNORM B1/Q1 SN 198 898 5.2 UNI 9175 Classe 1 IM UNI 9177 Classe 1 US CA TB 117-2013
APPROVED OMOLOGATO	/	/	  PRODUCT CERTIFIED FOR LOW CHEMICAL EMISSIONS: UL COM/IGG UL 2818 170166-420	
CLEANING LAVAGGIO	   	   	   	   

Finishes / Finiture

Steel and stainless steel / Acciaio e acciaio inox




CR
Chromed steel
Acciaio cromato




ST
Satinized steel
Acciaio satinato




LU
Polished s/steel
Acciaio inox lucidato



AC
Brushed s/steel
Acciaio inox satinato




AC 316
Brushed s/steel AISI 316
for outdoor
Acciaio inox AISI 316 per
esterno



BS
Antique bronze steel
Acciaio bronzo anticato



OA
Antique brass steel
Acciaio ottone anticato




RM
Antique copper steel
Acciaio rame anticato



EC
Corten steel
Acciaio effetto Corten

Gold lacquered / Laccato oro




VOR

Aluminium / Alluminio




LU
Polished aluminium
Alluminio lucidato



AS
Satinized aluminium
Alluminio satinato




AA
Anodized aluminium
Alluminio anodizzato



TN
Titanium
Titanio

Beech / Faggio



FS
Bleached beech
Faggio sbiancato



W
Wenge
Wengé

Oak / Rovere



RS
Bleached oak
Rovere sbiancato



W
Wenge
Wengé

Colours are indicative. Pedrali reserves the right to modify or upgrade the product without prior notice.
I colori sono indicativi. Pedrali si riserva la facoltà di apportare modifiche o migliorie senza alcun preavviso.

Outdoor finishes / Finiture per esterno

















Powder coated cast-iron, steel and aluminium / Ghisa, acciaio e alluminio verniciato

BI100E White, textured-matt finish Bianco, finitura goffrata-opaca	BI200E White, textured-matt finish Bianco, finitura goffrata-opaca	BI300E White, smooth-matt finish Bianco, finitura liscia-opaca	SA100E Sand, textured-matt finish Sabbia, finitura goffrata-opaca	SA200E Sand, textured-matt finish Sabbia, finitura goffrata-opaca	GI100E Yellow, textured-matt finish Giallo, finitura goffrata-opaca	AR200E Orange, textured-matt finish Arancio, finitura goffrata-opaca
AR500E Orange, textured-matt finish Arancio, finitura goffrata-opaca	AR400E Orange, textured-matt finish Arancio, finitura goffrata-opaca	RA100E Pink, textured-matt finish Rosa, finitura goffrata-opaca	RO400E Red, textured-matt finish Rosso, finitura goffrata-opaca	RO200E Red, textured-matt finish Rosso, finitura goffrata-opaca	TEE Terracotta, textured-matt finish Terracotta, finitura goffrata-opaca	RUE Rust, textured-matt finish Ruggine, finitura goffrata-opaca
MGE Brown, textured-matt finish Marrone, finitura goffrata-opaca	AZ100E Light blue, textured-matt finish Azzurro, finitura goffrata-opaca	BL500E Blue, textured-matt finish Blu, finitura goffrata-opaca	BL300E Blue, textured-matt finish Blu, finitura goffrata-opaca	BL400E Blue, textured-matt finish Blu, finitura goffrata-opaca	VE100E Sage green, textured-matt finish Verde salvia, finitura goffrata-opaca	VE600E Green, textured-matt finish Verde, finitura goffrata-opaca
VE300E Forest green soft-touch, smooth-matt finish Verde bosco soft-touch, finitura liscia-opaca	6005E Green, smooth-glossy finish Verde, finitura liscia-lucida	BE100E Beige, textured-matt finish Beige, finitura goffrata-opaca	BE200E Beige, textured-matt finish Beige, finitura goffrata-opaca	ALE Aluminium, smooth-glossy finish Alluminio, finitura liscia-lucida	9007E Aluminium, smooth-matt finish Alluminio, finitura liscia-opaca	AGE Aluminium, textured-matt finish Alluminio, finitura goffrata-opaca
GAE Anthracite grey, textured-matt finish Grigio antracite, finitura goffrata-opaca	GNE Natural grey, textured-matt finish Grigio naturale, finitura goffrata-opaca	NPE Black, textured-matt finish Nero, finitura goffrata-opaca				

Colours are indicative. Pedrali reserves the right to modify or upgrade the product without prior notice.
I colori sono indicativi. Pedrali si riserva la facoltà di apportare modifiche o migliorie senza alcun preavviso.

Indoor finishes / Finiture per interno


Powder coated cast-iron, steel and aluminium / Ghisa, acciaio e alluminio verniciato

						
BI100 White, textured-matt finish Bianco, finitura goffrata-opaca	BI200 White, textured-matt finish Bianco, finitura goffrata-opaca	BI300 White, smooth-matt finish Bianco, finitura liscia-opaca	SA100 Sand, textured-matt finish Sabbia, finitura goffrata-opaca	SA200 Sand, textured-matt finish Sabbia, finitura goffrata-opaca	SA300 Sand, hammered-glossy finish Sabbia, finitura bucciata-lucida	GI100 Yellow, textured-matt finish Giallo, finitura goffrata-opaca
						
AR200 Orange, textured-matt finish Arancio, finitura goffrata-opaca	AR500 Orange, textured-matt finish Arancio, finitura goffrata-opaca	AR400 Orange, textured-matt finish Arancio, finitura goffrata-opaca	RA100 Pink, textured-matt finish Rosa, finitura goffrata-opaca	RO400 Red, textured-matt finish Rosso, finitura goffrata-opaca	RO200 Red, textured-matt finish Rosso, finitura goffrata-opaca	RO300 Red, textured-matt finish Rosso, finitura goffrata-opaca
						
TE Terracotta, textured-matt finish Terracotta, finitura goffrata-opaca	RU Rust, textured-matt finish Ruggine, finitura goffrata-opaca	MG Brown, textured-matt finish Marrone, finitura goffrata-opaca				


Colours are indicative. Pedrali reserves the right to modify or upgrade the product without prior notice.
I colori sono indicativi. Pedrali si riserva la facoltà di apportare modifiche o migliorie senza alcun preavviso.

Indoor finishes / Finiture per interno


Powder coated cast-iron, steel and aluminium / Ghisa, acciaio e alluminio verniciato



AZ100
Light blue,
textured-matt finish
Azzurro,
finitura goffrata-opaca




BL500
Blue,
textured-matt finish
Blu,
finitura goffrata-opaca




BL300
Blue,
textured-matt finish
Blu,
finitura goffrata-opaca



BL400
Blue,
textured-matt finish
Blu,
finitura goffrata-opaca



VE100
Sage green,
textured-matt finish
Verde salvia,
finitura goffrata-opaca




VE600
Green,
textured-matt finish
Verde,
finitura goffrata-opaca




VE300
Forest green soft-touch,
smooth-matt finish
Verde bosco soft-touch,
finitura liscia-opaca




6005
Green,
smooth-glossy finish
Verde,
finitura liscia-lucida




VE400
Green,
textured-matt finish
Verde,
finitura goffrata-opaca



BE100
Beige,
textured-matt finish
Beige,
finitura goffrata-opaca




BE200
Beige,
textured-matt finish
Beige,
finitura goffrata-opaca



AL
Aluminium,
smooth-glossy finish
Alluminio,
finitura liscia-lucida



9007
Aluminium,
smooth-matt finish
Alluminio,
finitura liscia-opaca



AG
Aluminium,
textured-matt finish
Alluminio,
finitura goffrata-opaca



GA
Anthracite grey,
textured-matt finish
Grigio antracite,
finitura goffrata-opaca



GN
Natural grey,
textured-matt finish
Grigio naturale,
finitura goffrata-opaca



_NERO
Black,
hammered-matt finish
Nero,
finitura bucciata-opaca